

MEGAPACK



Megapack is an all-in-one utility-scale energy storage system that is scalable to the space, power, and energy requirements of any site from 2 MWh to over 1 GWh. Megapack is optimized for cost, performance, and ease of installation, and includes a standard system warranty of up to 15 years.

FULLY INTEGRATED SYSTEM

Megapack ships with battery modules, bi-directional inverter, thermal management system, and AC main breaker all pre-installed and pre-tested within a single enclosure. This turnkey system is designed to have the industry's fastest, lowest cost installation without sacrificing performance or reliability.

OPTIMIZATION SOFTWARE

Proprietary optimization software, developed in parallel with the Megapack hardware, learns and predicts local energy patterns, offering autonomous charge and discharge and seamless SCADA integration. Fast-response controls can integrate co-located renewables and enable market participation.

ENHANCED SYSTEM SAFETY

Parallel DC/DC converters, integrated heating and cooling at the cell level, and dedicated hazard venting are just a few of the safety and hazard mitigation features built into Megapack. Designed to meet international safety standards, Megapack helps ensure ease-of-permitting wherever it's installed.

INDUSTRY-LEADING RELIABILITY

A vertically integrated product from hardware design and sourcing to software development, Megapack offers significant reliability advantages over the competition. These design advantages are exemplified by a cooling system optimized specifically for Megapack that provides superior heating and cooling while factoring its HVAC energy consumption into its performance, and module-level DC/DC converters that can keep the system running uninterrupted in case of a partial failure.

LOWEST ENGINEERING, PROCUREMENT, AND CONSTRUCTION (EPC) COSTS

Megapack is shipped onsite fully assembled and pre-tested, offering customers the world's fastest utility-scale energy storage installation. Once on site, Megapack only requires seismic anchoring and connection of AC conductors and a communication cable. The EPC benefit is clear: no other current utility-scale solution offers such a simplified process.

GLOBAL SERVICE FOOTPRINT

As a vertically-integrated manufacturer and supplier, Tesla provides a streamlined service offering on all components of Megapack. With Tesla, customers enjoy a single point of contact through all stages of product life. Our operational fleet of 2+ GWh provides valuable data that informs our maintenance models and our performance guarantees, and the entire Megapack system is covered by a standard warranty of up to 15 years, with the option of a 20-year Capacity Maintenance Agreement (CMA) in certain cases.

MEGAPACK SPECIFICATIONS

Specifications shown here are indicative and subject to change.

Flexible offering designed for utility-scale projects

- Modular inverter Powerstages allow greater configuration flexibility
- Supports Capacity Maintenance Agreements (CMA)
- Integrate solar PV with DC coupling (future feature)

Proven inverter and battery technology drives design efficiency

- One Megapack includes up to 17 independent battery modules
- Configurable for 2 to 6+ hour charge/discharge cycles
- Best-in-class site-level energy density

Turnkey solution enables rapid and cost-effective deployment

- Up to 40% expected reduction in EPC costs compared to Powerpack
- Pre-assembled and pre-tested at Tesla's Gigafactory
- No DC connections required onsite



ELECTRICAL

AC Voltage	400–480 VAC 3-phase
------------	---------------------

Nominal Frequency	50 or 60 Hz
-------------------	-------------

Continuous Charge/Discharge Duration	2 to 6+ hours
--------------------------------------	---------------

AC Power/Energy Available per Megapack ¹	2 hr: 1257 kW / 2514 kWh 4 hr: 739.5 kW / 2958 kWh
---	---

Inverter Size (at 480 VAC)	2 hr: Scalable up to 1540 kVA 4 hr: Scalable up to 910 kVA
----------------------------	---

PV	Interface: Direct DC Coupled Max VoC: 1500 Vdc Max Imp: 2390 Adc
----	--

Megapack is a customizable energy system capable of being sized according to customer needs. Below are specifications for standard system sizes available without customization.

STANDARD SYSTEM SPECIFICATIONS

	AC Power/Energy Available per Megapack ¹	Roundtrip System Efficiency ¹
2 Hour Light	1005.5 kW / 2011 kWh	87.0%
2 Hour Standard	1257 kW / 2514 kWh	87.0%
4 Hour Light	522 kW / 2088 kWh	90.5%
4 Hour Standard	739.5 kW / 2958 kWh	90.5%

¹ Nominal energy at 25°C (77°F) including thermal management loads, Day 1

MECHANICAL AND MOUNTING

Ingress Ratings	IP66/NEMA 3R (Main enclosure) IP20 (Thermal system)
-----------------	--

Unit Dimensions	W: 7125 mm (23 ft 5 in) D: 1600 mm (5 ft 3 in) H: 2516 mm (8 ft 3 in)
-----------------	---

Unit Maximum Weight ²	Standard: 25,400 kg (56,000 lbs) Light: 19,700 kg (43,430 lbs)
----------------------------------	---

Operating Ambient Temperature	–30°C to 50°C (–22°F to 122°F)
-------------------------------	--------------------------------

² Optimized for global payload limits

REGULATORY (Expected Listings)

Lithium-Ion Cells	NRTL listed to UL 1642
-------------------	------------------------

System	NRTL listed to UL 1973, 9540, 9540A, 1741 SA IEEE 1547 Compliant to grid codes and safety standards of all major markets
--------	--

COMMUNICATIONS

Protocol	Modbus TCP DNP3 Rest API
----------	--------------------------------

PV DC-COUPLED SPECIFICATIONS

Megapack is capable of being the grid connection point for solar PV plants. This is accomplished by integrating solar PV with Megapack using a Tesla PV Sidecar: a 16 input PV combiner box with disconnects and zonal monitoring. By eliminating the separate PV inverter, Tesla's DC-integrated solution reduces system level costs and minimizes the number of power conversion steps to improve overall site level efficiency. The Megapack architecture supports a wide range of DC/AC (solar PV) and power-energy (storage) ratios, providing the flexibility to optimize for any PV plus storage use case. Integrating the entire plant with a single control system, Tesla's solution provides a fast, seamless, and robust platform for solar PV ramp control and firm or dispatchable renewable power generation.

ELECTRICAL - AC INTERFACE

Battery Power/Energy Available (Net AC) per Megapack¹	Scalable battery module quantity. 2 hr: Up to 1257 kW / 2514 kWh 4 hr: Up to 739.5 kW / 2958 kWh
---	--

Shared Solar/Battery Inverter Size (at 480 VAC)	Scalable up to 1540 kVA at 70kVA increments
--	---

¹ Nominal energy at 25°C (77°F) including thermal management loads

MECHANICAL AND MOUNTING

Ingress Ratings	IP66/NEMA 3R (Main enclosure) IP20 (Thermal system)
------------------------	--

Unit Dimensions	W: 830 mm (2 ft 9 in) D: 1600 mm (5 ft 3 in) H: 2516 mm (8 ft 3 in)
------------------------	---

Unit Maximum Weight	500 kg (1100 lbs) for PV Sidecar
----------------------------	----------------------------------

ELECTRICAL - PV DC INTERFACE

PV Interface Type	Direct DC Coupled, via Tesla provided PV Integration Unit No PV DC/DC Converter
--------------------------	--

PV Interface Ratings	Max VoC: 1500 Vdc Max Imp: 2390 Adc
-----------------------------	--

Maximum Power Point Tracking	MPPT Min V: 734 Vdc MPPT Max V: 961 Vdc Curtailment via MPPT or zonal disconnects
-------------------------------------	---

PV Inputs	Input Zone Count: 16 Input Size: 250-400 Adc Contactors and IGBT disconnects per zone Zonal current and voltage monitoring
------------------	---

COMMUNICATIONS

Protocol	Modbus TCP DNP3 Rest API
-----------------	--------------------------------

