

DO NOT SCALE. ALL DIMENSIONS TO BE CHECKED ON SITE AND VERIFIED PRIOR TO COMMENCING WORK/MANUFACTURE. ANY DISCREPANCIES TO BE REPORTED TO THE OFFICE.
THIS DRAWING IS PROTECTED BY COPYRIGHT. IT MAY NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS FOR ANY PURPOSE WITHOUT THE WRITTEN PERMISSION OF WEATHERHEAD SHOP DESIGN.

CoreLine Trunking	
CAD Key	Description
A13.4WB	CoreLine Trunking LL234X LED905840 PSD WB 7 WH A 45 watt 3400mm Long, 4500lm, 4000K (cool white) LED DALI Self Contained Trunking System Wide Beam, Finish White.
A21.7WB	CoreLine Trunking LL217X LED455840 PSD WB 7 WH A 45 watt 1700mm Long, 4500lm, 4000K (cool white) LED DALI Self Contained Trunking System Wide Beam, Finish White.
A31.7WB/EL3	CoreLine Trunking LL217X LED455840 PSD WB 7 EL3 WH A 45 watt 1700mm Long, 4500lm, 4000K (cool white) LED DALI Self Contained Trunking System Wide Beam, with 3-Hr Integral Emergency, Finish White.
A13.4VWB	CoreLine Trunking LL234X LED905840 PSD VWB 7 WH A 90 watt 3400mm Long, 9000lm, 4000K (cool white) LED DALI Self Contained Trunking System Very Wide Beam, Finish White.
A21.7VWB	CoreLine Trunking LL217X LED455840 PSD VWB 7 WH A 45 watt 1700mm Long, 4500lm, 4000K (cool white) LED DALI Self Contained Trunking System Very Wide Beam, Finish White.
A31.7WB/EL3	CoreLine Trunking LL217X LED455840 PSD WB 7 EL3 WH A 45 watt 1700mm Long, 4500lm, 4000K (cool white) LED DALI Self Contained Trunking System Very Wide Beam, with 3-Hr Integral Emergency, Finish White.
ST	CoreLine Trunking LL192 MB SW EXEP C17-2 WH A 170mm Long CoreLine Starter Kit Finish White.
B17	Luminaire Floodlight mini BVP150 LED33840 PSU VWB100 Wall mounted floodlight, Symmetric distribution, 27W, 2500lm.
B20	WT120C LED345840 PSD L1600mm - 3400LM Convex LED Surface Mounted LED IP65 Linear DALI Luminaire, LED Module, system flux 3400 lm, 33W, 1500mm Length.
B20-EL3	WT120C LED345840 PSD L1600mm EL3 - 3400LM Convex LED Surface Mounted LED IP65 Linear DALI Luminaire, LED Module, system flux 3400 lm, 33W, 1500mm Length, With 3-Hour Integral Emergency EL3.
B30	WT120C LED405840 PSD L1200mm - 4000LM Convex LED Surface Mounted LED IP65 Linear DALI Luminaire, LED Module, system flux 4000 lm, 41W, 1200mm Length.
B30-EL3	WT120C LED405840 PSD L1200mm EL3 - 4000LM Convex LED Surface Mounted LED IP65 Linear DALI Luminaire, LED Module, system flux 4000 lm, 41W, 1200mm Length, With 3-Hour Integral Emergency EL3.
SM BKO	SM BKO LED905840 PSD L170 NMI ELD Non- Maintained surface mounted emergency LED finished IP65 215 high lumen output unit.
B40	SM BKO EM LED SHN DALI EM LED Maintained wall mounted Emergency LED "EXIT" sign with "Straight On" arrow, ISO7010 "Straight Down" arrow, ISO7010 "Left" arrow, ISO7010 "Right Arrow" arrow, ISO7010
B120	RC1348 LED375840 PSD W60.00 DC Convex LED Recessed Mounted LED DALI, Office Compliant, Luminaire, system flux 3600 lm, 40W, 600x600mm.
RC1348-EL3	RC1348 LED375840 PSD W60.00 EL3 DC Convex LED Recessed Mounted LED DALI, Office Compliant, Luminaire, system flux 3600 lm, 40W, 600x600mm, With 3-Hour Integral Emergency EL3.
B150-U	Suspended Blade LED Edge LH Exit Sign DALI-4ip High output white light LED Edge LH Exit sign suspended from the ceiling. (Order Arrow Up Legend kit separately)
B40	WT120C LED405840 PSD L1600mm - 4000LM Convex LED Surface Mounted LED IP65 Linear DALI Luminaire, LED Module, system flux 4000 lm, 39W, 1500mm Length.
B40-EL3	WT120C LED405840 PSD L1600mm EL3 - 4000LM Convex LED Surface Mounted LED IP65 Linear DALI Luminaire, LED Module, system flux 4000 lm, 39W, 1500mm Length, With 3-Hour Integral Emergency EL3.
B60	WL151V LED125840 PSD WH Ceiling or Wall Surface Mounted IP65 DALI Luminaire, system flux 12000 lm, 100W, 340mm Dia, Finish White.
B60-EL3	WL151V LED125840 PSD WH EL3 Ceiling or Wall Surface Mounted IP65 DALI Luminaire, system flux 12000 lm, 100W, 340mm Dia, Finish White, With 3-Hour Integral Emergency EL3.
B200	CORE WALL LED17-355 PSU IP65 OA BK set at 350mA Emergency version.
B200 - EL3	CORE WALL LED17-355 PSU IP65 OA BK EL3 set at 350mA Emergency version.

NOTE: All Emergency lighting and Exit sign positions to be coordinated alongside Co-Op Fire Exit strategy. Exact locations to be coordinated by on-site installing contractor ensuring that all points of emphasis are covered, i.e. fire fighting equipment, fire call points etc.

22/04/21 - Technical Review Submission

Date	Rev	Description

weatherhead

Weatherhead Shop Designers Limited
10 Strashleigh View
Lee Mill Industrial Estate
Devon
PL21 9GS
Tel: 01752 690798
Fax: 01752 690850
Website: www.weatherheadgroup.com
Email: info@weatherheadgroup.com

Project Address:
EPSOM
9 Upper High Street
Epsom
Surrey
KT17 4QY

Drawing Title:
Lighting

Asset Underlay:
P9 F4 M0

Hub No.	Scale
TBC	1:50@A1

Drawing No:
TBC - 2021 - 004 -

NOTE: Luminaires adjusted for beams. Final details to be co-ordinated by installing contractor.

NOTE: Plant lighting layout indicative due to limited information.

BOH ceiling heights assumed.

NOTE: T-Bar mounted at 2.4m AFFL.

NOTE: CoreLine trunking suspended at 2.8m AFFL

CUSTOMER ENTRANCE/EXIT

GOODS ENTRANCE

NOTE: All Emergency Exit signage positions to be coordinated alongside Co-Op Fire Exit strategy. Exact locations to be coordinated by on-site installing contractor.

NOTE: All Emergency exit signs to be suspended/mounted between 2m-2.5mtrs.

LIGHTING	
	Sales lights A DB1/6L1
	Sales lights B DB1/5L1
	BOH lights A DB1/10L3
	BOH lights B DB1/11L2
	BOH lights C DB1/19L1
	Basement lights DB1/4L3
	Exterior lights rear DB1/20L2

