



**NOTES.**  
 ALL DIMENSIONS ARE IN mm (UNO)  
 FOUNDATION SIZES ARE THE MINIMUM REQUIRED ASSUMING GROUND BEARING CAPACITY OF 100kN/m<sup>2</sup>  
 DEVIATION FROM DATUM LEVEL AT TOP OF GATE FOUNDATIONS NOT TO EXCEED ±10  
 NOMINAL RUNNING CLEARANCE UNDER GATE IS 50mm  
 M16 STUDDING TO BE LEFT 100mm ABOVE FOUNDATION LEVEL  
 M16 NUTS SHOULD BE INSTALLED ABOVE & BELOW BASEPLATES ALLOW GROUT FOR LEVELING.

**MATERIALS.**  
 POSTS: 150 x 150 SHS  
 RUNNING TUBE: 140 MONORAIL  
 RAILS: 95 x 60 JAKCURED  
 STILES: 95 x 60 JAKCURED  
 INTERNAL FRAME: 50 x 25 RHS

**FINISH.**  
 GALVANISED TO BS EN ISO 1461  
 TIMBER: JAKCURED

**Jacksons Fencing**

Stowting Common, Near Ashford,  
 Kent. TN25 6BN  
 Telephone: 01233 750393  
 Fax: 01233 750403  
 www.jacksons-fencing.co.uk

DO NOT SCALE – IF IN DOUBT ASK

- ② 11/04/2023 Left Hand Hang as Approved
- ① 29/03/2023 Overall site length reduced
- ① 28/03/2023 Original Issue

Drawn NM  
 Date 28/03/2023  
 Checked  
 Size A3 Scale NTS U.O.S

TITLE 1.8m High x 3.0m Opening  
 Manual Rye Cantilever Sliding Gate

CUSTOMER LSB Fencing  
 ACK No. 2277824 (Buzby)

Drawing No.  
 JF 1007390  
 Sheet 1 of 2

This Drawing Is The Property Of H.S. Jackson & Son (Fencing) Ltd, And May Not Be Copied Or Reproduced In Any Way Without Prior Written Permission.